

Two - Stage Direct Drive Reciprocating Air Compressors







Fitting all your needs



Duplex

Simplex



Reliable as ever





Technical Specification

Model	Power		Comp. speed	Maximum Working Pressure		Free air delivery		Dimensions in mm			Weight	Air receiver
	НР	kW	rpm	bar (g)	psi (g)	lpm	cfm	length	breadth	height	kg	litre
TS 03 LD	3.0	2.2	950	12	175	261	9.2	1310	570	1020	160	160
TS 05 LD	5.0	3.7	960	12	175	439	15.5	1590	595	1045	190	220
TS 07 LD	7.5	5.6	960	12	175	680	24	1640	635	1110	255	220
TS 10 LD*	10.0	7.5	960	12	175	906	32	1915	635	1175	400	500
TS 15 LD*	15.0	11	960	12	175	1359	48	1911	782	1183	510	500

• Free air delivery measured in accordance with IS 5456 at a rated pressure of 10 kg/cm²

• Due to continuous engineering improvement, technical specifications are subject to change without prior notice.


• *Only available as duplex (10HP - 2 x 5HP and 15HP - 2 x 7.5HP)

Genuine Spares

For enhancing performance and productivity



Typical Compressed air supply system



Distributed by



ELGI EQUIPMENTS PTY LTD.,

Unit 1, 33 Kingsbury Street, Brendale QLD 4500, Australia. T: 07 3106 0589<mark>, E:</mark> enquiry@elgi.com.au, <mark>W</mark>: www.elgi.com.au

