



SW110 – HOT/COLD WATER CLEANER

SPECIFICATIONS

1650 P.S.I. (110 Bar) Pump Pressure
2400 P.S.I. Turbo Pressure (Optional)
12 Litres per Minute Pump Volume
240 Volt 3 H.P. Electric Motor
1450 RPM Industrial Machine
15 AMP Plug

STANDARD EQUIPMENT

10 Metres High Pressure Hose
Insulated On/Off Pistol Assembly
Double Lance Assembly
High and Low Pressure Mode
Adjustable Chemical Injector with Bottle
Operators and Parts Manuals
Bypass Shutdown Timer

<u>FEATURES</u>	<u>BENEFITS</u>
Interpump with Ceramic Pistons and Brass Head	→ Anodised crankcase and oversized bearings → Longer pump life, non corrosive pump head
Water By-Pass Cooling Tank	→ Reduces potential damage to the pump in bypass
Inlet Water Filter	→ Stops debris from scoring pistons and seals
Pressure Gauge	→ Easily monitor pump performance
Powder Coated Zinc Annealed Chassis	→ Resistant to corrosion
Adjustable thermostat for hot water temperature control	→ Set the ideal temperature for any application
Bypass Shutdown Timer	→ Increases life of the machine by shutting down when not in use