



# Chicago Pneumatic



People.  
Passion.  
Performance.

Complete On-site Solutions

# SOLUTIONS WHERE AND WHEN YOU NEED THEM

Chicago Pneumatic has built a real game changing line up when it comes to delivering on-site, air, power and light. Building on over 120 years of knowledge, our latest portfolio is our most innovative and toughest to date. The word toughness optimizes the Chicago Pneumatic brand. You will see toughness, coupled with superior portability and efficiency across the entire range.





# The Red Rock Air Compressor Range

The range of Red Rock air compressors are the latest and toughest edition to the Chicago Pneumatic portfolio. When it comes to this range of air compressors, we know what you are looking for: Portable, Powerful and Tough.

**Portable:** All models can be towed behind a normal passenger car with no special driving license needed

**Powerful:** Power up to two breakers with effortless ease. You can also get a generator included in the package if you wish.

**Tough:** The Red Rock canopy is made from extra tough polyethylene, protecting the working parts and ensuring your compressor looks and performs to its maximum, day in and day out.

In addition we have multiple options available to ensure the compressor exactly fits your needs, including **weather options, quality air options, towing options and multiple points of customization.**



		CPS 2.0	CPS 2.5	CPS 2.0-12	CPS 3.0	CPS 3.5
Normal effective working pressure	bar (g)	7	7	12	7	7
	psi (g)	100	100	175	100	100
Free air delivery	cfm	70	90	80	105	135
	m3/min	2,0	2,5	2,0	3,0	3,5
Output power	l/s	33	42	33	50	58
	kVA	-	-	-	-	-
Sound pressure level (LpA) at 7m	dB(A)	70	70	70	70	70
Sound power level (LwA)	dB(A)	98	98	98	98	98
Max. Ambient temperature at sea level	°C	50	50	50	50	50
Min. Starting temperature	°C	-10	-10	-10	-10	-10
Min. Starting temperature (Cold start aid)	°C	-20	-20	-20	-20	-20

#### Engine

		Kubota D 722	Kubota D 902	Kubota V 1505	Kubota V 1505	Kubota V 1505
Model						
Number of cylinders		3	3	4	4	4
Power output @ normal shaft speed	kW	14,9	18,5	26,5	26,5	26,5
Full load RPM	rpm	3400	3400	3000	3000	3000
Unload RPM	rpm	2000	2000	1850	1850	1850

#### Capacity

Engine oil	l	3,7	3,6	5,5	5,5	5,5
Compressor oil	l	5,5	5,5	7,7	7,7	7,7
Fuel tank	l	27	27	60	60	60

#### Box unit dimensions

Length	mm	1540	1540	1950	1950	1950
Width	mm	960	960	1180	1180	1180
Height	mm	900	900	1120	1120	1120
Weight	kg	440	440	650	650	650

#### Undercarriage dimensions

Type	Trailer mounted with adjustable towbar (without brakes)					
Length	mm	1960	1960	2300	2300	2300
Width	mm	1230	1230	1350	1350	1350
Height	mm	1250	1250	1430	1430	1430
Weight	kg	500	500	< 750	< 750	< 750



### Standard Features:

- All models below 750 KG
- Red Rock polyethylene canopy
- Easy service guarantee with all parts easily accessible and spin on components
- 10 models to choose from
- Spillage free frame



						With Generator	
		CPS 3.5-10	CPS 4.5	CPS 5.0	CPS 5.5	CPS 2.5 G	CPS 3.5 G
Normal effective working pressure	bar (g)	10	7	7	7	7	7
	psi (g)	150	100	100	100	100	100
Free air delivery	cfm	135	160	175	191	90	135
	m <sup>3</sup> /min	3,5	4,5	5,0	5,4	2,5	3,5
	l/s	58	77	83	90	42	58
Output power	kVA	-	-	-	-	6,5   12	6,5   12
Sound pressure level (LpA) at 7m	dB(A)	70	70	70	70	70	70
Sound power level (LwA)	dB(A)	98	98	98	98	98	98
Max. Ambient temperature at sea level	°C	50	50	50	50	50	50
Min. Starting temperature	°C	-10	-10	-10	-10	-10	-10
Min. Starting temperature (Cold start aid)	°C	-20	-20	-20	-20	-20	-20

### Engine

Model		Kubota V 1505 T	Kubota V 1505 T	Kubota V 1505 T	Deutz D2011L03	Kubota V 1505 T	Kubota V 1505 T
Number of cylinders		4	4	4	3	4	4
Power output @ normal shaft speed	kW	33	33	33	36	26,5 (33)	33
Full load RPM	rpm	3000	3000	3000	2750	3000	3000
Unload RPM	rpm	1850	1850	1850	1850	1850	1850

### Capacity

Engine oil	l	5,5	5,5	5,5	8,5	5,5	5,5
Compressor oil	l	7,7	7,7	7,7	8	7,7	7,7
Fuel tank	l	60	60	60	80	60	60

### Box unit dimensions

Length	mm	1950	1950	1950	1950	1950	1950
Width	mm	1180	1180	1180	1180	1180	1180
Height	mm	1120	1120	1120	1120	1120	1120
Weight	kg	650	650	650	650	650	650

### Undercarriage dimensions

Type		Trailer mounted with adjustable towbar (without brakes)			ANB	Trailer mounted with adjustable towbar (without brakes)	
Length	mm	2300	2300	2300	3670	2300	2300
Width	mm	1350	1350	1350	1450	1350	1350
Height	mm	1430	1430	1430	1250	1430	1430
Weight	kg	< 750	< 750	< 750	940	< 750	< 750

# The CPDG Mobile Generator Range

CPDG generators have been designed to meet the tough demands of the construction industry. Using proven technology, sturdy design and ease of operation, the CPDG provides you with a dependable source for all your electrical power needs. With integrated forklift slots and a lifting beam, the CPDG range of generators are easy to move and designed to be highly impact resistant. Other features include easy to read gauges, easy to access maintenance points and a reinforced structure. The CPDG generators are available with a galvanized canopy. It meets applicable CE requirements for use in European markets.

## Standard Features:

- Galvanized canopy
- Centrally reinforced structure
- Lifting beam
- Spillage free frame with forklift slots
- Lockable fuel filler neck
- Robust terminal board that is suitable for connection with or without clamps
- Analogue control panel
- Easy drainage of all liquids
- Additional fuel filter with water separator

## Available Options:

- Battery isolation switch
- Exhaust rain cap
- Power sockets panel
- Oil sump pump
- Cold weather operation
- Engine coolant heater
- External fuel connections
- Battery charger
- Skid with forklift slots
- ATB panels
- High capacity fuel tank



		CPDG 9	CPDG 14	CPDG 20	CPDG 30	CPDG 40
<b>Electrical data</b>						
Rated voltage	V	400 / 230	400 / 230	400 / 230	400 / 230	400 / 230
Prime power	kVA	9	13,8	20	30	42
Standby power	kVA	10	16	21,5	33	46
Power Factor cos phi		0,8	0,8	0,8	0,8	0,8
<b>Fuel consumption</b>						
Fuel consumption @ 100% PRP load	l/h	2,5	3,5	5,1	7	10
Fuel autonomy at full load	h	22	15,7	10,8	15	10,4
Fuel tank capacity	l	55	55	55	105	105
<b>Engine</b>						
Model		Kubota D1105-BG2	Kubota D1703M-BG	Kubota V2403M-BG	Kubota V3300-BG2	Kubota V3800DI-T-BG-E3
Speed	rpm	1500	1500	1500	1500	1500
Engine exhaust compliance 97/68/CE		Below 19 kW	Below 19 kW	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA
<b>Noise level</b>						
Sound power level (LwA)	dB(A)	90	90	91	92	91
Sound pressure level (LpA)	dB(A) at 7 m	63	63	64	66	65
<b>Weight and dimensions</b>						
Length	mm	1750	1750	1750	2200	2200
Width	mm	840	840	840	940	940
Height	mm	1215	1215	1215	1270	1270
Weight	kg	600	600	720	945	1015



		CPDG 60	CPDG 85	CPDG 105	CPDG 120	CPDG 150	CPDG 200
<b>Electrical data</b>							
Rated voltage	V	400 / 230	400 / 230	400 / 230	400 / 230	400 / 230	400 / 230
Prime power	kVA	61	84	104	119	150	200
Standby power	kVA	66	92	114	131	164	220
Power Factor cos phi		0,8	0,8	0,8	0,8	0,8	0,8
<b>Fuel consumption</b>							
Fuel consumption @ 100% PRP load	l/h	14,8	19,6	24	28	34,5	45,8
Fuel autonomy at full load	h	11	12	10	8	11	8
Fuel tank capacity	l	160	230	230	230	375	375
<b>Engine</b>							
Model		John Deere 4045HFU81	John Deere 4045HFU82	John Deere 4045HFU82	John Deere 4045HFU82	John Deere 6068HFU82	John Deere 6068HFU82
Speed	rpm	1500	1500	1500	1500	1500	1500
Engine exhaust compliance 97/68/CE		EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA
<b>Noise level</b>							
Sound power level (LwA)	dB(A)	95	95	95	97	97	97
Sound pressure level (LpA)	dB(A) at 7 m	69	69	69	71	71	71
<b>Weight and dimensions</b>							
Length	mm	2300	3000	3000	3000	3350	3350
Width	mm	1130	1150	1150	1150	1170	1170
Height	mm	1500	1600	1600	1600	1700	1700
Weight	kg	1500	1850	1900	2100	2520	2650

# The **CPSG** Generator Range

CPSG units are built to withstand tough working conditions, making them ideal for operators seeking a consistent source of power for 24/7 operations, across a wide variety of applications in non regulated countries or stationary applications within European market. Built with only quality components, galvanized canopies, meticulous assembly and vigorous testing, guarantee long and reliable performance. A wide variety of options provide the functionality needed to match all power demands.

## Standard Features:

- Galvanized canopy
- Spillage free frame
- Advanced control panel that enables users to control and operate it remotely
- Lockable fuel filling cap
- Easy fuel tank cleaning access to prevent damage from contaminants.
- Easy drainage of all liquids

## Available Options:

- Additional fuel filter with water separator
- Battery isolation switch
- Engine coolant heater
- External fuel tank connections
- Battery charger
- Open frame
- Lifting beam
- High-capacity fuel tank
- Power Transfer Box

CPSG		CPSG9	CPSG14   CPSG13	CPSG20   CPSG18	CPSG30   CPSG27	CPSG40	CPSG60   CPSG55	CPSG85   CPSG80	CPSG105   CPSG95	CPSG130   CPSG110
<b>Performance Data</b>										
Rated frequency	Hz	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60
Rated voltage*	V	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127	400/230   220/127
Prime power	kVA	9   11	13,6   16	20   23	30   36	42   49	60   70	85   102	105   122	130   143
Standby power	kVA	10   12,6	16   18,8	21,5   23,6	33   37	47   54	66   73	95   108	116   132	143   153
<b>Fuel Consumption</b>										
Fuel tank capacity	l	55	55	55	105	105	115	215	215	215
Fuel consumption at 75% PRP	l/h	2,1   2,38	2,8   3,4	3,9   4,6	5,7   6,6	7,4   8,7	9,7   11,8	14,5   17,1	17,6   21,5	22   25,6
Fuel autonomy	h	26   23,1	19,6   16,2	14,1   12	18,4   15,9	14,2   12,1	11,9   9,7	14,8   12,6	12,2   10	9,8   8,4
<b>Engine</b>										
Model		Kubota D1105-BG2	Kubota D1703-M-BG	Kubota V2403-M-BG	Kubota V3300-BG	Kubota V3800DI-T-BG 2	Cummins 4BTA-3.9-G2	Cummins 6BT-5.9-G2	Cummins 6BT5.9-G2	Cummins 6BTAA-5.9-G2
Speed	rpm	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800
Speed control		Mechanical	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
<b>Alternator</b>										
Model		ECP3-1L/4A	ECP3-3L/4	ECP28-M/4A	ECP28-VL/4A	ECP32-3S/4A	ECP32-2L/4A	ECP34-1S/4A	ECP34-2S	ECP34-1L
Excitation system		MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX
AVR model		DSR	DSR	DSR	DSR	DSR	DSR	DSR	DSR	DSR
<b>Weight and dimensions</b>										
Length	mm	1750	1750	1750	2220	2220	2280	2900	2900	2900
Width	mm	840	840	840	940	940	950	1090	1090	1090
Height	mm	1155	1155	1155	1185	1185	1260	1685	1685	1685
Weight	kg	585	670	700	930	980	1220	1774	1840	1882
Mechanical structure		Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed

\* For other voltage configuration, please consult.





CPSG	CPSG200   CPSG185	CPSG300   CPSG280	CPSG410   CPSG360	CPSG460   CPSG420	CPSG525   CPSG455	CPSG570   CPSG510	CPSG635   CPSG550	CPSG680   CPSG645	CPSG750   CPSG675
------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------

#### Performance Data

	Hz	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60
Rated frequency	Hz	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60	50   60
Rated voltage*	V	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277	400/230   480/277
Prime power	kVA	200   232	300   352	410   450	460   526	524   572	571   642	635   692	680   808	752   849
Standby power	kVA	220   253	330   378	470   500	509   582	580   625	630   680	700   764	735   893	830   925

#### Fuel Consumption

	l	489	489	1079	1079	1079	1079	1079	1293	1293
Fuel tank capacity	l	489	489	1079	1079	1079	1079	1079	1293	1293
Fuel consumption at 75% PRP	l/h	31,7   37,5	46,5   56	65,1   74,7	72,9   83,4	83,4   92,9	94,2   106,6	103,8   114,2	109   127,7	119,1   134,4
Fuel autonomy	h	15,4   13	10,4   8,7	16,6   14,4	14,8   12,9	12,9   11,6	11,5   10,1	10,4   9,4	11,9   10,1	10,9   9,6

#### Engine

Model		Doosan P086 TI	Doosan P126 TI-II	Doosan P158 LE	Doosan DP158 LC	Doosan DP158 LD	Doosan DP180 LA	Doosan DP180 LB	Doosan DP222 LB	Doosan DP222 LC
Speed	rpm	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800
Speed control		Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic

#### Alternator

Model		ECO38-2S	ECO38-2L	ECO40-2S   ECO40-1S	ECO40-3S   ECO40-2S	ECO40-1L   ECO40-3S	ECO40-1.5L   ECO40-1L	ECO40-2L   ECO40-1.5L	ECO40-2L   ECO40-VL	ECO43-1SN   ECO40-VL
Excitation system		MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX	MAUX
AVR model		DSR	DSR	DER1	DER1	DER1	DER1	DER1	DER1	DER1

#### Weight and dimensions

	mm	3840	3840	4800	4800	4800	4800	4800	5200	5200
Length	mm	3840	3840	4800	4800	4800	4800	4800	5200	5200
Width	mm	1470	1470	1870	1870	1870	1870	1870	1870	1870
Height	mm	1785	1785	2395	2395	2395	2395	2395	2535	2535
Weight	kg	2835	3215   3315	4508   4430	4771   4718	4924   4771	5095   5039	5301   5095	5871   5978	6155   5978
Mechanical structure		Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed	Soundproofed

\* For other voltage configuration, please consult.

# The **CPPG** Portable Generator Range



## **CPPG Inverter**

The day-to-day silent solution below 3kVA.

## **CPPG Standard**

The CPPG Standard Line offers straight forward gasoline generators with all the features you need for your occasional use built right in. They are designed to deliver stable electrical output and safe, user-friendly operation over a long service life.

## **CPPG Professional**

A generator for professionals by professionals, built for extensive and continuous use. Available with a gasoline or diesel engine, the CPPG Professional is extraordinarily versatile.

## **CPPG Advanced**

A top-of-the-line generator for heavy, all day operation. With several standard extras, simple controls, safe operations and an extended service life, the CPPG Advanced provides supreme reliability for intensive use in tough environments. Available with a gasoline or diesel engine.

## **CPPG Advanced+**

A sound proofed generator with the same features as the Advanced range, the CPPG Advanced+ is the perfect choice when working in noise restricted or dusty environments. The canopy not only serves as sound insulation but also protects the machine from dust.



CPPG	CPPG INVERTER				CPPG STANDARD			
	CPPG2i   CPPG2iW	CPPG3.5   CPPG3.5iW	CPPG2.3   CPPP2.5W	CPPG5   CPPG5.5W	CPPG5T	CPPG7   * CPPG7W	CPPG7T *	
<b>Generator data</b>								
Rated frequency	Hz	50   60	50   60	50   60	50   60	50	50   60	50
Rated voltage	V	230   120	230   120	230   240   120	230   240   120	400 / 230	230   240 / 120	400 / 230
Nominal power output	kVA	1,6	3,0	2,3   2,5	5	6,2	6,0   6,5	7,5
Peak power output	kVA	1,8	3,3	2,5   2,8	5,5	6,8	6,5   7,0	8,1
Power factor cos Phi		1	1	1	1	0,8	1	0,8
Fuel tank capacity	l	4	10	15	25	25	25	25
Fuel autonomy at nominal power	h	5	6	11	10	10	8	8
Sockets configuration		1 x SCH   2 x 3P20A	2 x SCH   2 x 3P20A + 1 x TL240	2 x SCH   2 x 3P20A + 1 x TL240	2 x SCH + 1 x 3P32A   4 x 3P20A + 1 x TL240	1 x SCH + 1 x 5P16A	2 x SCH + 1 x 3P32A   4 x 3P20A + 1 x TL240	1 x SCH + 1 x 5P16A

SCH: Schuko 2P+G 16A 3P16A: CEE 230V 2P+G 16A 3P32A: CEE 230V 2P+G 32A 5P16A: CEE 400V 3P+N+G 16A 3P20A: Nema 120 V 20A TL120: Nema 120V twist lock 20A TL240: Nema 240/120 V Twist Lock

Engine		CP148F Gasoline	CP170FD Gasoline	CP200FA Gasoline	CP390FD Gasoline	CP390FD Gasoline	CP420FD Gasoline	CP420FD Gasoline
Model								
Nominal speed	rpm	5000	3600	3000   3600	3000   3600	3000	3000   3600	3000
Power output	kWm	2,4	4,4	4,1	8,2	8,2	9	9
Displacement	cm3	79	212	196	389	389	420	420
Starter type		Recoil	Electric / Recoil	Recoil	Electric / Recoil	Electric / Recoil	Electric / Recoil	Electric / Recoil

Alternator		2	3	2,5	5   5,5	6,3	6   6,5	7,5
Power	kVA							

Noise level		65	63	70	72	72	76	76
Sound pressure level (LpA) at 7m	dB(A)							
Sound power level (LwA)	dB(A)	90	88	95	97	97	101	101

Weight and dimensions		500	580	590	675	675	680	680
Length	mm							
Width	mm	285	440	430	540	540	550	550
Height	mm	455	510	480	540	540	550	550
Weight	kg	21	45	52	79	79	83	85

CPPG	CPPG PROFESSIONAL GASOLINE						CPPG PROFESSIONAL DIESEL			
	CPPG3P	CPPG3.5P	CPPG5P	CPPG6.5P	CPPG7.5P	CPPG8P	CPPG4P*	CPPG4.5P*	CPPG6P*	CPPG7P*

<b>Generator data</b>											
Rated frequency	Hz	50	50	50	50	50	50	50   60	50	50   60	50
Rated voltage	V	230	230	230	400 / 230	230	400 / 230	230   240 / 120	400 / 230	230   240 / 120	400 / 230
Nominal power output	kVA	2,4	2,9	4,3	5,4	6,1	7	3,3   3,5	4	4,9   4,7	5,6
Peak power output	kVA	2,9	3,4	5,1	6,3	7,1	8,3	3,9   3,7	4,6	5,9   5,2	6,9
Power factor cos Phi		0,9	0,9	0,9	0,8	0,9	0,8	0,9   1	0,8	0,9	0,8
Fuel tank capacity	l	11	11	11	11	11	11	3,5	3,5	5,5	5,5
Fuel autonomy at nominal power	h	9,4	7	5	5	3,8	3,9	2,8	2,8	2,8   2,3	2,8
Sockets configuration		2 x SCH	2 x SCH	1 x SCH + 1 x 3P16A	1 x SCH + 1 x 3P32A	1 x SCH + 1 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A   1 x 3P20A + 1 x TL240	1 x SCH + 1 x 3P32A	1 x SCH + 1 x 5P16A   1 x 3P20A + 1 x TL240	1 x SCH + 1 x 3P16A + 1 x 5P16A

SCH: Schuko 2P+G 16A 3P16A: CEE 230V 2P+G 16A 3P32A: CEE 230V 2P+G 32A 5P16A: CEE 400V 3P+N+G 16A 3P20A: Nema 120 V 20A TL120: Nema 120V twist lock 20A TL240: Nema 240/120 V Twist Lock

Engine		Honda GX160 Gasoline	Honda GX200 Gasoline	Honda GX270 Gasoline	Honda GX270 Gasoline	Honda GX390 Gasoline	Honda GX390 Gasoline	Yanmar L70 Diesel	Yanmar L70 Diesel	Yanmar L100 Diesel	Yanmar L100 Diesel
Model											
Nominal speed	rpm	3000	3000	3000	3000	3000	3000	3000   3600	3000	3000   3600	3000
Power output	kWm	3,2	3,8	5,7	5,7	7,7	7,7	4,5   5,4	4,5	6,5   7,4	6,5
Displacement	cm3	163	196	270	270	389	389	320	320	435	435
Starter type		Recoil	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil

Alternator		2,7	3	4,2	7	6	7	4,2   7	7	5   6,5	7
Power	kVA										

Noise level		68	67	69	69	69	69	76	76	80	80
Sound pressure level (LpA) at 7m	dB(A)										
Sound power level (LwA)	dB(A)	96	95	97	97	97	97	101	101	105	105

Weight and dimensions		623	623	729	729	729	729	760	760	760	760
Length	mm										
Width	mm	409	409	500	500	500	500	540	540	540	540
Height	mm	500	500	536	536	536	536	560	560	560	560
Weight	kg	42	44	62	76	74	82	55   71	71	95	97

\* Not compliant with directive 2000/14/EC.

## CPPG Range continued

CPPG	CPPG ADVANCED GASOLINE						CPPG ADVANCED DIESEL				
	CPPG5A	CPPG6.5A	CPPG7.5A	CPPG8A	CPPG12A	CPPG14A	CPPG6A*	CPPG7A*	CPPG9A*	CPPG10A*	
<b>Generator data</b>											
Rated frequency	Hz	50	50	50	50	50	50	50	50	50	50
Rated voltage	V	230	400 / 230	230	400 / 230	230	400 / 230	230	400 / 230	230	400 / 230
Nominal power output	kVA	4,3	5,4	6,1	7,0	10,1	11,9	4,9	5,6	7,6	8,8
Peak power output	kVA	5,3	6,3	7,1	8,3	11,9	13,9	5,9	6,9	8,8	10,3
Power factor cos Phi		0,9	0,8	0,9	0,8	0,9	0,8	0,9	0,8	0,9	0,8
Fuel tank capacity	l	18	18	18	18	24	24	24	24	24	24
Fuel autonomy at nominal power	h	8,1	8,1	6,3	6,3	4,3	4,3	12,4	12,4	8,3	8,3
Sockets configuration		1 x SCH + 1 x 3P32A	1 x SCH + 1 x 3P32A	1 x SCH + 1 x 3P16A + 1 x 3P32A	1 x SCH + 1 x 5P16A	1 x SCH + 1 x 5P16A	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A + 1 x 3P32A	1 x SCH + 1 x 3P16A + 1 x 3P32A	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P32A + 1 x 5P16A

SCH: Schuko 2P+G 16A 3P16A: CEE 230V 2P+G 16A 3P32A: CEE 230V 2P+G 32A 5P16A: CEE 400V 3P+N+G 16A 3P20A: Nema 120 V 20A TL120: Nema 120V twist lock 20A TL240: Nema 240/120 V Twist Lock

<b>Engine</b>											
Model		Honda GX270 Gasoline	Honda GX270 Gasoline	Honda GX390 Gasoline	Honda GX390 Gasoline	Honda GX630 Gasoline	Honda GX630 Gasoline	Yanmar L100 Diesel	Yanmar L100 Diesel	Lombardini 25LD330 Diesel	Lombardini 25LD330 Diesel
Nominal speed	rpm	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000
Power output	kWm	5,7	5,7	7,7	7,7	12	12	6,5	6,5	10	10
Displacement	cm3	270	270	389	389	688	688	435	435	654	654
Starter type		Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric

<b>Alternator</b>											
Power	kVA	4,2	7	6	7	10	11,5	5	6	8	10

<b>Noise level</b>											
Sound pressure level (LpA) at 7m	dB(A)	69	69	69	69	68	68	80	80	80	80
Sound power level (LwA)	dB(A)	97	97	97	97	96	96	105	105	105	105

<b>Weight and dimensions</b>											
Length	mm	842	842	842	842	960	960	840	840	960	960
Width	mm	523	523	523	523	641	641	641	641	641	641
Height	mm	557	557	557	557	667	667	696	696	667	667
Weight	kg	69	81	89	92	190	187	115	125	159	162

CPPG	CPPG ADVANCED+ GASOLINE			CPPG ADVANCED+ DIESEL				
	CPPG12AS	CPPG14AS	CPPG4AS	CPPG6AS	CPPG7AS	CPPG9AS	CPPG10AS	

<b>Generator data</b>											
Rated frequency	Hz	50	50	50	50   60	50	50   60	50	50   60	50	50
Rated voltage	V	230	400 / 230	230	230   240 / 120	400 / 230	230   240 / 120	400 / 230	230   240 / 120	400 / 230	400 / 230
Nominal power output	kVA	10,1	11,9	3,4	4,8	5,6	7,6	5,6	7,6	9,1	9,1
Peak power output	kVA	11,9	13,9	4,1	5,9	6,9	8,8	6,9	8,8	10,6	10,6
Power factor cos Phi		0,9	0,8	0,9	0,9	0,8	0,9	0,8	0,9	0,8	0,8
Fuel tank capacity	l	24	24	18	24	24	24	24	24	24	24
Fuel autonomy at nominal power	h	4,4	4,3	14,5	12,4   10	12,4	8,3   8	12,4	8,3   8	8,3	8,3
Sockets configuration		1 x SCH + 1 x 3P16A + 1 x 3P32A	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A + 1 x 3P32A	1 x SCH + 1 x 3P16A + 1 x 3P32A   2 x 3P20A + 1 x TL240	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A + 1 x 3P32A   2 x 3P20A + 1 x TL240	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 1 x 3P16A + 1 x 3P32A   2 x 3P20A + 1 x TL240	1 x SCH + 2 x 3P16A + 1 x 5P16A	1 x SCH + 2 x 3P16A + 1 x 5P16A

SCH: Schuko 2P+G 16A 3P16A: CEE 230V 2P+G 16A 3P32A: CEE 230V 2P+G 32A 5P16A: CEE 400V 3P+N+G 16A 3P20A: Nema 120 V 20A TL120: Nema 120V twist lock 20A TL240: Nema 240/120 V Twist Lock

<b>Engine</b>											
Model		Honda GX630 Gasoline	Honda GX630 Gasoline	Yanmar L70 Diesel	Yanmar L100 Diesel	Yanmar L100 Diesel	Lombardini 25LD330 Diesel	Lombardini 25LD330 Diesel			
Nominal speed	rpm	3000	3000	3000	3000   3600	3000	3000   3600	3000			
Power output	kWm	12	12	4,5	6,5   7,4	6,5	10	10			
Displacement	cm3	688	688	320	435	435	654	654			
Starter type		Electric	Electric	Electric	Electric	Electric	Electric	Electric			

<b>Alternator</b>											
Power	kVA	9,5	11,5	4,1	6   6,5	6	8   10	10			

<b>Noise level</b>											
Sound pressure level (LpA) at 7m	dB(A)	61	61	68	65   69	65	69   72	69			
Sound power level (LwA)	dB(A)	89	89	96	93   97	93	97   100	97			

<b>Weight and dimensions</b>											
Length	mm	990	990	800	990	990	990	990			
Width	mm	602	602	520	602	602	602	602			
Height	mm	826	826	690	826	826	826	826			
Weight	kg	190	190	99	188	188	206	209			

\* Not compliant with directive 2000/14/EC.

# The **Light Tower** Portfolio

We have a light tower for any site, any conditions and importantly any budget. We have a wide range of LED options with choices on the canopy design and design features. Because of the harsh conditions that the light towers are likely to operate within, we focus on ensuring peak performance and optimizing lifespan and resale value. We also focus on allowing easy maintenance access to the machine, including service components and drains. All models have an environmentally friendly frame that prevents any excess fluid escaping.





## LIGHT TOWER

		CPLT V15	CPLT V15 LED	CPLT H5	CPLT H6 LED	CPLB 6 LED
<b>Performance data</b>						
Rated frequency	Hz	50   60	50   60	50	50	50
Rated voltage	VAC	230   120	230   120	230	230	230
Rated power (PRP)	kW	5,4   6,8	2,5   2,7	6	2,7	2,7
Operating temperature (min/max)	°C	-25 / 49	-25 / 50	-5 / 50	-20 / 40	-20 / 40
Sound power level (LwA)	dB(A)	92   94	86	90	90	88
Sound pressure level (LpA)	dB(A) at 7 m	71   73	63	65	65	63
<b>Engine</b>						
Model		Kubota Z482	Kubota Z482	Kubota D1105-EBG2	Hatz 1 B 50	Hatz 1 B 50
Speed	rpm	3000   3600	1500   1800	1500	1500	1500
Rated net output (PRP)	kW	6,9   8,1	2,7   3	7,5	3,5	3,5
Coolant		Water	Water	Water	Air	Air
Number of cylinders		2	2	3	1	1
<b>Alternator</b>						
Model		Sincro EK 2 MCT	Meccalte LT3/75	Meccalte LT3N-160/4	Linz E1C13S A/4	Linz E1C13S A/4
Rated output	kVA	6   7,5	3,5   4,5	8	5,5	5,5
Insulation / Enclosure protection	class/IP	H / 23	H / 21	H / 21	H / 21	H / 21
<b>Consumption</b>						
Fuel tank capacity	l	105	105	110	120	130
Fuel Autonomy	h	57   50	150	65	185	200
<b>Power output</b>						
Auxiliary power	kW	1,4   2	1	2,3	1,2	1,2
<b>Lights</b>						
Floodlights		Metal halide	LED	Metal halide	LED	LED
Wattage	W	4 x 1000	4 x 350	4 x 1000	4 x 350	4 x 350
<b>Mast</b>						
Type		Manual vertical, 5 section	Manual vertical, 5 section	Hydraulic	Hydraulic	Hydraulic
Rotation	degrees	360	360	340	340	340
Maximum height	mm	7500	7500	9000	8000	8000
Maximum wind speed	km/h	80	80	80	80	80
<b>Enclosure and trailer</b>						
Trailer		DOT US Compliant Unibody trailer with 4 point leveling system. For EU homologated check availability		EU Road homologated fix or adjustable towbar, or site trailer		-
Base frame		Spillage free frame			Spillage free frame	
Enclosure		Gull-wing Red Rock doors			Galvanized steel canopy and powder coating paint	
<b>Dimensions inc. Transport fix towbar and weight</b>						
Length	mm	1670	1670	2700	2300	1160
Width	mm	1100	1100	1300	1280	1160
Height	mm	2500	2500	2310	2485	2500
Weight	kg	694	702	1195	1050	980



## LIGHT TOWER

### Performance data

		CPLB 2	CPLB 2 LED
Rated frequency	Hz	50	50
Rated voltage	VAC	230	230

### Lights

		CPLB 2	CPLB 2 LED
Floodlights		Metal halide	LED
Wattage	W	4 X 400	4 X 160

### Mast

		CPLB 2	CPLB 2 LED
Type		Manual	Manual
Rotation	degrees	0	0
Maximum height	mm	7000	7000
Maximum wind speed	km/h	80	80

### Dimensions inc. Transport fix towbar and weight

		CPLB 2	CPLB 2 LED
Length	mm	1200	1200
Width	mm	800	800
Height	mm	2140	2140
Weight	kg	241	250

### Variants

Standard Plug / Socket - Variant 1		CEE 32A Inlet Plug & Outlet socket
Standard Plug - Variant 2		Schuko 16A Inlet Plug

## Light Tower Selection Guide

	CPLT V15	CPLT V15 LED	CPLT H5	CPLB 6 LED	CPLB 2	CPLB 2 LED
<b>Fuel efficiency</b>	** 2 l/h	*** 0.7 l/h	** 1.7 l/h	*** 0.5 l/h	*** 0 l/h	*** 0 l/h
<b>Area coverage</b>	*** 4000 m2	*** 5000 m2	*** 4000 m2	*** 5000 m2	** 2000 m2	** 3000 m2
<b>Safety features</b>	** Manual vertical mast	** Manual vertical mast	*** Hydraulic vertical mast	*** Hydraulic vertical mast	** Manual vertical mast	** Manual vertical mast
<b>Lamps durability</b>	** 6000 hrs	*** 30000 hrs	** 6000 hrs	*** 30000 hrs	** 6000 hrs	** 30000 hrs
<b>Transport efficiency</b>	** 16 units in a truck	** 16 units in a truck	** 8 units in a truck	** 22 units in a truck	*** 32 units in a truck	*** 32 units in a truck
<b>Extra features</b>	Red Rock canopy	Red Rock canopy	Heavy-duty	Compact footprint	Easy plug into any power source	Easy plug into any power source

\*\*\* Great Choice \*\* Good Choice

**SERVICE MADE EASY.  
EASY ACCESS  
TO CHANGE ALL PARTS.  
SERVICE KITS TO KEEP YOU  
RUNNING**

We have one simple goal – to keep you running. Chicago Pneumatic focusses on ease of doing business and reducing service time; quick access to parts is paramount to that promise. Our global network has all the parts, lubricants and accessories you need, ensuring we keep your product in tip-top condition and delivering exactly what you need it to deliver.







NEWS



20



## Over 100 Years of Experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.



For more information, please contact your CP partner:

Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.